

AT-GS900/8E

Unmanaged Gigabit Ethernet Switches



AT-GS900/8E

8 port 10/100/1000T unmanaged switch, ext P/S

ECO-Friendly

The AT-GS900/8E eco friendly switch conforms with Allied Telesis' commitment to environmentally friendly processes and products. It is designed to minimize power consumption through the use of a high efficiency power supply and a low power chipset.

With a low 3.8W typical power consumption*, an EnergyStar rated power supply, and a reduction in power during after-work hours (overnight mode) – as well as other power saving features included as standard, the Allied Telesis AT-GS900/8E truly lives up to it's name as an 'eco friendly' switch.

Not only does this help the planet by reducing the carbon footprint of each switch, it also lowers the Total Cost of Ownership (TCO) to the user, as the product costs less to run, and has improved reliability.

With all of these power saving features, the new eco friendly AT-GS900/8E saves the user up to 60% in power consumption over our previous version (see power saving table).

High Performance

Providing powerful 10/100/1000 switching solutions for desktop and small network environments, the Allied Telesis GS900 series of unmanaged switches features full auto-negotiating 10/100/1000T ports. These ports enable the switches to detect the speed and duplex modes of attached devices, enabling them to automatically configure for the best possible performance.

Flexibility

Available in 5 and 8 port models, Allied Telesis lets you decide which size is best for your network. Reduces your cost by allowing you to only pay for the ports you need.

Simplified Installation

The GS900 series switches require minimal configuration and can be installed in minutes via wall-mount or desktop. The 10/100/1000T copper ports on the GS900 series are fully auto-negotiating, allowing the switches to connect to all other 10Mbps Ethernet, 100Mbps Fast Ethernet, or 1000Mbps Gigabit Ethernet devices. Equipped with MDI/MDI-X ports for easy connection to other hubs and switches, the GS900 series offers a natural migration path from legacy networks and a cost-effective introduction to Gigabit Ethernet. Finally, easy to read front panel LEDs show ongoing switch status and simplify troubleshooting.

Quality and Reliability

Allied Telesis is a worldwide leader in unmanaged Ethernet switches. Shipping more than 250,000 unmanaged switches every year, Allied Telesis offers proven reliability and industry recognized quality.

Key Features

- Wirespeed performance
- Non-blocking architecture
- Auto-negotiation Gigabit ports
- Auto MDI/MDI-X on TX ports
- Transparent to VLAN packets
- Full-duplex flow control

Power-saving Features

- Maximum switch power consumption – 4.9W
- Typical switch power consumption - 3.8W*
- External, EnergyStar rated power supply
- Overnight mode - when PCs are powered off, the switch reduces power
- Power down mode
- Measure and minimize - checks the lengths of the cable and sends only enough power for specific cable length



*6 ports connected with 3M cables

AT-GS900/8E | Unmanaged Gigabit Ethernet Switches

Performance

14,880pps for 10Mbps Ethernet
 148,800pps for 100Mbps Ethernet
 1,488,000pps for 1000Mbps Ethernet

Throughput 11.9Mpps
 Switching capacity 16Gbps

MAC addresses Up to 4K

Packet buffer 832KB

Half/full-duplex 1K
 Auto-negotiation
 MDI/MDI-X

Interface Connections

10/100/1000T RJ-45

Power Characteristics

Rated input voltage 100-240V AC
 Rated input frequency 50/60Hz
 Rated input current 0.3A
 Input voltage range AC 100~240V
 Output voltage DC 7.5V
 Output current 1.0A
 Output watt 7.5Watt
 Power consumption 3.975Watt

Power Saving % Chart

| Ports | Status | Non-green vs Green Power Saving % | | | |
|----------------|-------------------------------|-----------------------------------|---------|------------|---------|
| | | 3m cable | | 100m cable | |
| | | AC side | DC side | AC side | DC side |
| Overnight mode | | 59.1% | 25.2% | 60.3% | 23.6% |
| 8 port | Only link, no traffic | 36.0% | 27.2% | 26.8% | 16.2% |
| | Smartbit, 100% utilization TX | 35.5% | 26.6% | 26.2% | 19.4% |
| 7 port | Only link, no traffic | 36.7% | 27.8% | 27.5% | 17.5% |
| | Smartbit, 100% utilization TX | 36.7% | 26.4% | 27.8% | 17.3% |
| 6 port | Only link, no traffic | 38.1% | 29.3% | 28.6% | 18.3% |
| | Smartbit, 100% utilization TX | 38.0% | 28.0% | 28.4% | 17.5% |
| 5 port | Only link, no traffic | 38.8% | 28.6% | 30.4% | 19.0% |
| | Smartbit, 100% utilization TX | 39.4% | 30.0% | 31.4% | 21.4% |
| 4 port | Only link, no traffic | 41.9% | 29.6% | 34.7% | 22.0% |
| | Smartbit, 100% utilization TX | 41.1% | 31.3% | 34.2% | 24.8% |
| 3 port | Only link, no traffic | 43.6% | 31.1% | 38.0% | 24.2% |
| | Smartbit, 100% utilization TX | 45.1% | 32.7% | 39% | 28.0% |
| 2 port | Only link, no traffic | 48.3% | 32.0% | 43.6% | 27.7% |
| | Smartbit, 100% utilization TX | 48.4% | 36.1% | 43.8% | 30.5% |

Environmental Specifications

Operating temp. 0°C to 40°C (32°F to 104°F)
 Non-operating temp. -25°C to 70°C (-13°F to 158°F)
 Operating humidity 5% to 90% non-condensing
 Storage humidity 5% to 95% non-condensing

Technical Specifications

Physical Characteristics

Dimensions 17.1cm x 9.8cm x 2.8cm
 (H x W x D) (6.73in x 3.86in x 1.1in)

Weight .389g (0.857lbs)

Wall-mount or Desktop

All units come with wall-mount hardware

Standards and Compliance

IEEE 802.3 10T Ethernet
 IEEE 802.3u 100TX Fast Ethernet
 IEEE 802.3ab 1000T Gigabit Ethernet
 IEEE 802.3z Full-duplex
 IEEE 802.3x Flow control

Electrical/Mechanical Approvals

UL 1950
 FCC/EN55022 Class A
 VCCI Class A
 C-Tick
 EN60950 (TUV)
 EN55024
 CE

Ordering Information

AT-GS900/8E

8 port 10/100/1000T unmanaged switch, external P/S

Where xx = 10 for U.S. power cord
 20 for no power cord
 30 for U.K. power cord
 40 for Australian power cord
 50 for European power cord

USA Headquarters | 19800 North Creek Parkway | Suite 100 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

www.alliedtelesis.com

© 2009 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000314 Rev.A